

REVISIONS			
REV	DESCRIPTION	DATE	APPROVED

DESCRIPTION:

SHIELDED CABLE: 3 twisted pairs, 24 A.W.G. FEP Teflon
 Colors: black&red, blue&yellow, grey&white
 Overall shield: aluminum polyester w/24 A.W.G.stranded
 tinned copper drain wire
 Outer covering: Natural flamarrest jacket
 nominal O.D.: .171

NOTE: Similar to BELDEN 82503 except custom wire colors.

FIRST USED	TOLERANCE UNLESS OTHERWISE SPECIFIED FRACTIONS 1/32 (.794 MM) .XX ±.01 (.254 MM) .XXX ±.005 (.127 MM) .XXXX ±.0005 (.0127 MM) ANGLES ±1 DEGREE SURFACE FINISH 125/ ✓ OR BETTER	DRAWN MF 111395	MFG. APPROVED	GETTYS GETTYS CORPORATION 2701 N. GREENBAY RD. RACINE, WI, U.S.A.					
MATERIAL		CHECKED	RELEASED <i>GETS 1/17</i>		TITLE CABLE, FEEDBACK				
FINAL FINISH		ENG. APPROVED <i>Gettys 1/17</i>	ISSUED	SIZE A	FSCM NO	DWG NO 140-008-0013	SCALE NONE	EDN 036018	SHEET 1

NOTE: UNLESS OTHERWISE SPECIFIED.
 1. REMOVE ALL BURRS AND SHARP EDGES.
 2. CHFR FIRST THD. ALL TAPPED HOLES
 3. _____
 4. _____

THIS DOCUMENT AND ALL INFORMATION CONTAINED OR IMPLIED HEREIN IS THE PROPERTY OF GETTYS. IT SHALL NOT BE DUPLICATED OR COMMUNICATED TO OTHERS NOR USED FOR PURPOSES OTHER THAN THOSE FOR WHICH IT WAS SPECIFICALLY FURNISHED.